




egeplast

egeplast

SLM[®] DCT

Detection and proof of non-damage



Dimension	OD 25 - 630 mm
SDR rating	SDR 7.4 9 11 13.6 17 (more available on request)
Application	Drinking water
Pipe design	Medium pipe: Black, PE 100-RC
	Detection layer: Two aluminium strips applied in spirals
	Protective layer: Layer extruded onto the surface in a continuous manufacturing process, made of modified polyethylene PEplus, blue (colour coding for drinking water) Green triple stripes to mark a pipe serving as a protective layer pipe
Features	Proof of damage-free installation Enhanced safety in operation Permanent detection possible With an abrasion-resistant protective layer, also for trenchless installation methods
Marking	Coloured meter marking of the medium pipe and protective layer in accordance with the relevant standard Execution as embossed marking (others on request)
Delivery forms	Sticks of 6, 12 or 20 m Coiled bundles of 100 m Other lengths on request Drums on customer request
Product standards	DIN 8074/75 EN 12201 DVGW GW 335
Tests and certification	TÜV SÜD MUC-KSP-A 3003
Regulations / Installation- and processing guidelines	DVGW GW 320 GW 321 GW 323 W 400 DVS 2207-1 DIN EN 805 DIN 4124 egeplast Processing Guidelines
Services and Support	Clamping jaws Protective layer peeling devices Instructions at the construction site Project planning Site monitoring



Created: 08.12.2022 JK

Checked: 08.12.2022 JK

Approval: 08.12.2022 JK

Version: 1.0

This datasheet is for information purposes only. egeplast accepts no guarantee with respect to the up-to-dateness, accuracy and completeness of the information. egeplast reserves the right to revise and supplement this document without prior notice.

egeplast international GmbH

Robert-Bosch-Straße 7 • 48268 Greven • Tel. +49 2575 9710-0 • Fax +49 2575 9710-110 • info@egeplast.de • www.egeplast.de

