




egeplast

egeplast SLM[®] DCS

To monitor critical infrastructures



Dimension
25-630 mm

Dimension	OD 25 - 630 mm
SDR rating	SDR 7.4 9 11 13.6 17 (more available on request)
Application	Sewage
Pipe design	Medium pipe: Black, PE 100-RC
	Conductive strips: Two aluminium strips applied in spirals
	Protective layer: Layer extruded onto the surface in a continuous manufacturing process, made of modified polyethylene PEplus, brown (colour coding for sewage) Green triple stripes to mark a protective layer pipe
Features	Leakage monitoring of the pipeline as an early warning system Precise pipe and damage tracking With an abrasion-resistant protective layer, also for trenchless installation methods
Marking	Coloured meter marking of the medium pipe and protective layer in accordance with the relevant standard Execution as embossed marking (others on request)
Delivery forms	Sticks of 6, 12 or 20 m Coiled bundles of 100 m Other lengths on request Drums on customer request
Product standards	DIN 8074/75 EN 12201
Tests and certification	TÜV SÜD MUC-KSP-A 3003
Regulations / Installation- and processing guidelines	DVGW GW 320 GW 321 GW 323 W 400 DVS 2207-1 DIN EN 805 DIN 4124 egeplast Processing Guidelines
Services and Support	Clamping jaws Protective layer peeling devices Instructions at the construction site Project planning Site monitoring Commissioning



Created: 08.12.2022 JK

Checked: 08.12.2022 JK

Approval: 08.12.2022 JK

Version: 1.0

This datasheet is for information purposes only. egeplast accepts no guarantee with respect to the up-to-dateness, accuracy and completeness of the information. egeplast reserves the right to revise and supplement this document without prior notice.

egeplast international GmbH

Robert-Bosch-Straße 7 • 48268 Greven • Tel. +49 2575 9710-0 • Fax +49 2575 9710-110 • info@egeplast.de • www.egeplast.de

