



egeplast

egeplast

# egeLiner

Folding pipe system for trenchless pipe rehabilitation



Dimension  
145 - 500 mm

Dimension	DN 145 - 500 mm
SDR rating	SDR 17 (DN 500 in SDR 21 only)
Application	Drinking water   Pressure pipe applications   Trenchless pipe deformation methods (Close-fit)
Material	PE 100-RC (MRS 10)
Pipe design	Pipe string with thermomechanically deformed cross-section
Features	Low space requirements at the construction site, small excavation pits   Short rehabilitation times and low amount of civil engineering works   Low cross section reduction - Close-fit   Enhanced flow characteristics owing to reduced roughness of the pipe walls
Colour	Black with blue stripes
Maximum operating pressure (MOP)	10 bar (SF 1.25)   DN 500 8 bar (SF 1.25)
Delivery forms	Drum
Tests and certification	DVGW   NPM
Regulations / Installation- and processing guidelines	In accordance with DIN EN ISO 11298   Following DVGW GW 335- A2   EN 12201

Created: 29.07.2025 JK

Checked: 29.07.2025 JK

Approval: 29.07.2025 JK

Version: 1.1

This datasheet is for information purposes only. egeplast accepts no guarantee with respect to the up-to-dateness, accuracy and completeness of the information. egeplast reserves the right to revise and supplement this document without prior notice.

egeplast international GmbH

Robert-Bosch-Straße 7 • 48268 Greven • Tel. +49 2575 9710-0 • Fax +49 2575 9710-110 • info@egeplast.de • www.egeplast.de

