



egeplast

egeplast

egeLiner

Folding pipe system for trenchless pipe rehabilitation

Dimension
150-432 mm

Dimension	DN 150 - 432 mm
SDR rating	SDR 17
Application	Gas Pressure pipe applications Trenchless pipe deformation methods (Close-fit)
Material	PE 100 (MRS 10)
Pipe design	Pipe string with thermomechanically deformed cross-section
Features	Low space requirements at the construction site, small excavation pits Short rehabilitation times and low amount of civil engineering works Low cross section reduction - Close-fit
Colour	Black with orange-yellow stripes
Maximum operating pressure (MOP)	5 bar (SF 2.0)
Delivery forms	Drum
Tests and certification	DVGW
Regulations / Installation- and processing guidelines	In accordance with DIN EN ISO 11299 Following DVGW GW 335- A2 EN 1555

Created: 08.12.2022 JK

Checked: 08.12.2022 JK

Approval: 08.12.2022 JK

Version: 1.0

This datasheet is for information purposes only. egeplast accepts no guarantee with respect to the up-to-dateness, accuracy and completeness of the information. egeplast reserves the right to revise and supplement this document without prior notice.

egeplast international GmbH

Robert-Bosch-Straße 7 • 48268 Greven • Tel. +49 2575 9710-0 • Fax +49 2575 9710-110 • info@egeplast.de • www.egeplast.de

