




egeplast

egeplast

SLM[®] 3.0

Protective layer pipe system for damage-free installation



Dimension	OD 25 - 630 mm
SDR rating	SDR 11 17 (more available on request)
Application	Gas
Pipe design	<p>Medium pipe: Black, PE 100-RC</p> <p>Protective layer: Layer extruded onto the surface in a continuous manufacturing process, made of modified polyethylene PEplus, orange-yellow (colour coding for gas)</p> <p>Green triple stripes to mark a pipe serving as a protective layer pipe</p>
Features	The additional protective layer (wear layer) allows for damage-free installation of the new pressure pipe DVS-compliant welding: Butt welding without layer cut-back possible Trenchless installation without any shortening of service life or reducing the safety factor
Marking	Coloured meter marking of the medium pipe and protective layer in accordance with the relevant standard Execution as embossed marking (others on request)
Delivery forms	Sticks of 6, 12 or 20 m Coiled bundles of 100 m Other lengths on request Drums on customer request
Product standards	DIN 8074/75 EN 1555 DVGW GW 335
Tests and certification	TÜV SÜD MUC-KSP-A 3003
Regulations / Installation- and processing guidelines	DVGW GW 320 GW 321 GW 323 G 472 DVS 2207-1 DIN EN 12007 DIN 4124 egeplast Processing Guidelines
Services and Support	Clamping jaws Protective layer peeling devices Instructions at the construction site Project planning Site monitoring



Created: 08.12.2022 JK

Checked: 08.12.2022 JK

Approval: 08.12.2022 JK

Version: 1.0

This datasheet is for information purposes only. egeplast accepts no guarantee with respect to the up-to-dateness, accuracy and completeness of the information. egeplast reserves the right to revise and supplement this document without prior notice.

egeplast international GmbH

Robert-Bosch-Straße 7 • 48268 Greven • Tel. +49 2575 9710-0 • Fax +49 2575 9710-110 • info@egeplast.de • www.egeplast.de

