



Tender Specification

Socket pressure pipes egeMDR with an axially force-locking socket, 9010® RC^{plus} version

Preliminary note:

Socket pressure pipe egeMDR, 9010® RC^{plus} version, for installation without embedding in sand; for drinking water; in accordance with DIN 8074/8075, DIN EN 12201; verified in accordance with both DIN 8075 and DVGW GW 335 Part A2; made of PE 100-RC in accordance with PAS 1075; with extra-wide blue stripes for visual inspection, layer thickness of the stripes amounts to 10% of wall thickness.

Pipe with a welded and axially force-locking socket made of a single coupler with short transition piece; joint body verified in accordance with DVGW GW 335 Part B2.

A valid DVGW certificate for pipes and socket for the medium drinking water is available.

The piping is to be stored and transported on the building site in compliance with the KRV guidelines.

Product: Socket pressure pipe egeMDR, 9010® RC^{plus} version
for drinking water

Manufacturer: egeplast international GmbH
Robert-Bosch-Str. 7
D-48268 Greven
Tel.: +49.2575.9710-0
Fax: +49.2575.9710-110
e-mail: info@egeplast.de
<http://www.egeplast.de>

Specification of services: Socket pressure pipe egeMDR, 9010® RC^{plus} version
For drinking water
made of PE 100-RC, with an axially force-locking socket
OD _____ mm, SDR _____
delivered as straight lengths of 6 / 12 m

Deliver _____ running metres and install according to DIN and appropriate installation guidelines as drinking water pipe: _____ €/ running metre



egeMDR socket elbow 9010[®] RC^{plus}, seamless, with a single-sided and axially force-locking socket, lip-seal 3S, OD_____ mm, SDR _____, 15°, 30° or 45°

_____€/piece.

egeMDR socket elbow 9010[®] RC^{plus}, seamless, with a single-sided and axially force-locking socket, lip-seal 3S, OD_____ mm, SDR _____, 60° or 90°

_____€/piece.

egeMDR double socket elbow 9010[®] RC^{plus}, seamless, with a double-sided and axially force-locking socket, lip-seal 3S, OD_____ mm, SDR _____, 15°, 30° or 45°

_____€/piece.

egeMDR double socket elbow 9010[®] RC^{plus}, seamless, with a double-sided and axially force-locking socket, lip-seal 3S, OD_____ mm, SDR _____, 60° or 90°

_____€/piece.

egeMDR socket-tee PE 100, with an all-sided axially force-locking socket, lip-seal 3S, OD_____ mm, SDR _____

_____€/piece.

egeMDR socket-tee PE 100, reduced, with an all-sided axially force-locking socket, lip-seal 3S, OD_____ mm, SDR _____

_____€/piece.

Double socket made of PE 100-RC, with an axially force-locking socket, lip-seal 3S, OD_____ mm, SDR _____

_____€/piece.



egeplast

Flanged socket made of PE 100-RC, with an axially force-locking socket, lip-seal 3S, with a welded HP-flange drilled in accordance to EN 1092-1, PN 10, DN/OD_____ mm, SDR _____,

_____€/piece.