

## Tender Specification Socket pressure pipes egeMDR with an axially force-locking socket, SLM<sup>®</sup> version

Preliminary note:

Socket pressure pipe egeMDR, SLM<sup>®</sup> version, for installations without sand bed; for drinking water; in accordance with DIN 8074/8075, DIN EN 12201; verified in accordance with both DIN 8075 and DVGW GW 335 Part A2; made of PE 100-RC in accordance with PAS 1075; pipes with dimensions according to DIN 8074 with an outer protective layer, consisting of a core pipe made of PE 100-RC, black, and an additional protective layer made of polyolefin, with yellow-green stripes; pipe-ends stripped on length of insertion and chamfered in the factory.

Pipe with a welded and axially force-locking socket made of a single coupler with short transition piece; joint body verified in accordance with DVGW GW 335 Part B2.

A valid DVGW certificate for pipes and socket for the medium drinking water is available.

The piping is to be stored and transported on the building site in compliance with the KRV guidelines.

Product:	Socket pressure pipe egeMDR, SLM® version
	for drinking water
Manufacturer:	egeplast international GmbH
	Robert-Bosch-Str. 7
	D-48268 Greven
	Tel.: +49.2575.9710-0
	Fax: +49.2575.9710-110
	e-mail: info@egeplast.de
	http://www.egeplast.de

Specification of services: Socket pressure pipe egeMDR, SLM<sup>®</sup> version for drinking water made of PE 100-RC, with an axially force-locking socket OD\_\_\_\_\_mm, SDR \_\_\_\_\_ delivered as straight lengths of 6 / 12 m

Deliver\_\_\_\_\_ running metres and install according to DIN and appropriate installation guidelines as drinking water pipe: \_\_\_\_\_\_ € / running metre



ageMDD appliest allow DE 100 DC, appendices, with a single sided and avially force leaking appliest
egeMDR socket elbow PE 100-RC, seamless, with a single-sided and axially force-locking socket,
lip-seal 3S, OD mm, SDR,
15°, 30° or 45°
€/piece.
egeMDR socket elbow PE 100-RC, seamless, with a single-sided and axially force-locking socket,
lip-seal 3S, OD mm, SDR,
60° or 90°
<i>El</i> picco
€/piece.
egeMDR double socket elbow PE 100-RC, seamless, with a double-sided and axially force-locking socket,
lip-seal 3S, OD mm, SDR,
15°, 30° or 45°
€/piece.
egeMDR double socket elbow PE 100-RC, seamless, with a double-sided and axially force-locking socket,
lip-seal 3S, OD mm, SDR,
60° or 90°
€/piece.
egeMDR socket-tee PE 100, with an all-sided axially force-locking socket, lip-seal 3S,
OD mm, SDR
€/piece.
egeMDR socket-tee PE 100, reduced, with an all-sided axially force-locking socket, lip-seal 3S,
OD mm, SDR
€/piece.
Double control made of DE 400 DO with an evially force to bit is a solution of 00. OD
Double socket made of PE 100-RC, with an axially force-locking socket, lip-seal 3S, OD mm, SDR

\_\_\_\_€/piece.



Flanged socket made of PE 100-RC, with an axially force-locking socket, lip-seal 3S, with a welded HP-flange drilled in accordance to EN 1092-1, PN 10, DN/OD\_\_\_\_ mm, SDR \_\_\_\_\_,

\_\_\_€/piece.